

SL30WN

National III emission standard.

- ▶ Engine model: Weichai WP6G125E201
- ▶ Rated power: 92 kW/2000 rpm
- ▶ Operating weight: 10.3 t

Product features

Another small offering in wheel loaders, the SL30WN still offers mid-range performance for its size. It has auto-lubrication in the bucket and arm joints. The sealed glass cabin offers a wide field of vision and a shock absorbing seat for greater driver comfort and safety.



SHANTUI

VALUE THAT WORKS

PT. BADAK PRIMA LESTARI

Kawasan Industri Millenium, Jl. Millenium 15 Blok I-2 No. 3A, Desa Peusar,
Kecamatan Panongan, Kabupaten Tangerang, Banten 15710 INDONESIA

Tel: +62 59986616 / 30 , Fax.: +62 59986847


www.badakprima.co.id


SL30WN


Technical specifications:


	Standard Arm	Extended Arm	Long Arm
Overall length	7043 mm	7170 mm	7290 mm
Overall width	2484 mm	2484 mm	2484 mm
Overall height	3235 mm	3235 mm	3235 mm


SL30WN

	GENERAL SPECIFICATIONS	Operating weight	10300 kg
		Related loading	3000 kg
		Bucket capacity	1.7 m³
		Maximum lifting force	105 kN
		Static tipping load (full turn)	6000 kg
		Dumping height (Standard arm/Extended/Long)	2875/3057/3200 mm
		Dumping reach (Standard arm/Extended/Long)	955/906/886 mm

	ENGINE	Engine model	Weichai WP6G125E201
		Type	In-line, water-cooled, 4-cylinder, direct injection, turbocharged
		Rated power	92 kW
		Rated speed	2000 rpm
		Displacement	6.75 L
		Maximum torque	540 N·m
		Minimum fuel consumption	217 g/kW·h

	TRAVEL SPEED	Gear	1st	2nd	3rd	4th
		Forward	0~7 km/h	0~12 km/h	0~23 km/h	0~37 km/h
		Reverse	0~8.3 km/h	0~28 km/h	-	-

	AXLES AND FINAL DRIVES	DRIVE SYSTEM		Four-wheel drive
		Gradeability		30°
		Maximum traction		110 kN
		BRAKE SYSTEM:	Service brakes	Air-on-oil callper disc brakes
			Parking brake	Disc brake on gearbox output shaft
		STEERING SYSTEM:	Type	Articulated type, full-hydraulic power steering
			Maximum steering angle	36° each direction
			The center of outside tire	5100 mm
			The center of outside bucket	5920 mm
		TIRES	Type	17.5-25 12PR
			Pattern level	L3
			Center distance of tires	1856 mm
			Wheel base	2700 mm

	HYDRAULIC SYSTEM	Hydraulic cycle time (rated load in bucket)	Lifting time/ Lifting, dumping and lowering	5.1/9.0 s

OVERALL DIMENSIONS

► THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.

