

SL60W-2

Tubeless tires combined with upgraded performance, strength and efficiency.

- ▶ Engine model: Weichai WD10G240E21
- ▶ Rated power: 175 kW/2200 rpm
- ▶ Operating weight: 21.0 t

Product features

The best feature of this model, like its 60W cousin, is not only its sheer size, but also its tubeless tires that offer deeper treads for greater traction. It offers even larger capacity, though does not sacrifice anything when it comes to turn radius and turning angle.



SHANTUI

VALUE THAT WORKS

 **PT. BADAQ PRIMA LESTARI**

Kawasan Industri Millenium, Jl. Millenium 15 Blok I-2 No. 3A,
Desa Peusar, Kecamatan Panongan, Kabupaten Tangerang, Banten 15710 INDONESIA

Tel: +62 59986616 / 30 , Fax.: +62 59986847

E-mail: sales@badakprima.co.id

www.badakprima.co.id

SL60W-2


Technical specifications:


Overall length: 8692 mm


Overall width: 3082 mm


Overall height: 3548 mm


SL60W-2

	GENERAL SPECIFICATIONS	Operating weight	21000 kg		
		Related loading	6000 kg		
		Bucket capacity	3.5 m ³		
		Maximum lifting force	179 kN		
		Static tipping load (full turn)	12000 kg		
		Dumping height	3314 mm		
		Dumping reach	1205 mm		

	ENGINE	Engine model	WEICHAI WD10G240E21		
		Type	In-line, water-cooled, 6-cylinder, direct injection, turbocharged		
		Rated power	175 kW		
		Rated speed	2200 rpm		
		Displacement	9.726 L		
		Maximum torque	912 N-m		
		Minimum fuel consumption	230 g/kW-h		

	TRAVEL SPEED	Gear	1st	2nd	3rd	4th
		Forward	0~8 km/h	0~15 km/h	0~24 km/h	0~38 km/h
		Reverse	0~8 km/h	0~15 km/h	0~24 km/h	0~38 km/h

	AXLES AND FINAL DRIVES	DRIVE SYSTEM		Four-wheel drive	
		Gradeability		30°	
		Maximum traction		172 kN	
		BRAKE SYSTEM:	Service brakes	Air over oil four-wheel dual-loop disc brake system	
			Parking brake	Automatically air-cut brake, disc brake	
		STEERING SYSTEM:	Type	Articulated type, full-hydraulic power steering	
			Maximum steering angle	35° each direction	
			The center of outside tire	6808 mm	
		TIRES	The center of outside bucket	7665 mm	
			Type	26.5-25 16PR	
			Pattern level	L3	
			Center distance of tires	2250 mm	
Wheel base	3400 mm				

	HYDRAULIC SYSTEM	Hydraulic cycle time (rated load in bucket)	Lifting time/ Lifting, dumping and lowering	5.5/11.8 s

OVERALL DIMENSIONS

▶ THE SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. THE PICTURES MAY INCLUDE OPTIONS. THE ACTUAL COLOR & APPEARANCE OF THE PRODUCT MAY DIFFER FROM WHAT IS SHOWN.

